

# DIVVEE

# SPLIT

ENERGY MANAGEMENT SYSTEM

## SPECIFICATIONS

**CURRENT RATING:** 40 AMPS**VOLTAGE:** 240/208 AC VOLTS SINGLE PHASE**CYCLE TIMER FACTORY SETTING:** 2 HOURS**FREQUENCY:** 50-60HZ PHASE**ENCLOSURE:** NEMA1**AGENCY APPROVAL:** CQAIUS LISTED**BOX DIMENSIONS:** 12"X 12"X 6"**KNOCK-OUT DIMENSIONS:** ½", ¾", 1", 1¼", 1½"**WEIGHT:** 10LBS (4.5KG)

Introducing the all new **DIVVEE Split**. This industrial-duty device allows you to seamlessly share power between two EV chargers on an adjustable 2-hour cycle. Beyond EV charging, the DIVVEE Split is certified to manage power for hot tubs, HVAC systems, workshops, and more. By leveraging your existing electrical infrastructure, it eliminates the need for costly panel upgrades, ensuring reliable and efficient power distribution. Enhance your electrical system with the DIVVEE Split and experience advanced energy management tailored to your needs.

LEVEL 2 EV CHARGING NO PANEL UPGRADE 40 AMP CURRENT ANY DEVICE UP TO 240V INDUSTRIAL-DUTY 

# MORE FROM LOADSHARE

## DIVVE 40

ENERGY MANAGEMENT SYSTEM

**CURRENT RATING:** 40 AMPS

**RELAY SENSITIVITY:** 1 AMP

**VOLTAGE:** 240/208 AC VOLTS SINGLE PHASE

**RELAY RESPONSE TIME:** 200MS

**FREQUENCY:** 50-60HZ PHASE

**ENCLOSURE:** NEMA 1

**AGENCY APPROVAL:** CQAIUS LISTED

**BOX DIMENSIONS:** 12" X 12" X 4"

**KNOCK-OUT DIMENSIONS:** ½", ¾", 1", 1"

**WEIGHT :** 8LBS (3.7KG)



## DIVVE 60

ENERGY MANAGEMENT SYSTEM

**CURRENT RATING:** 60 AMPS

**RELAY SENSITIVITY:** 2 AMPS

**VOLTAGE:** 240/208 AC VOLTS SINGLE PHASE

**RELAY RESPONSE TIME:** 200MS

**FREQUENCY:** 50-60HZ PHASE

**ENCLOSURE:** NEMA 1

**AGENCY APPROVAL:** CQAIUS LISTED

**BOX DIMENSIONS:** 12" X 12" X 6"

**KNOCK-OUT DIMENSIONS:** ½", ¾", 1", 1¼", 1½"

**WEIGHT :** 10LBS (4.5KG)

